

LOG YARD SAFETY PROCEDURES

Employee _____ Trainer _____ Date _____

- Ground personnel must wear high visibility hard hats and high visibility vests to enable equipment operators to more readily see them.
- Maintain solid log decks to prevent logs from rolling and causing harm.
- Build stable loads by ensuring logs are well saddled.
- Do not swing logs near or over anyone.
- Log loaders must maintain at least 36 inches of counterweight clearance.
- Locate ground workers before moving equipment.
- Maintain a clear view of the direction of travel.
- If a loader is not equipped with an automatic bi-directional alarm, sound the horn before moving the loader.
- Keep your machine in good condition.
- Wear personal protective equipment: hard hat when outside the cab, leg, eye and hearing protection and heavy duty boots while operating a chain saw. Work boots that provide ankle support are required for all employees.
- Use steps and grab rails. Don't jump from the machine.
- Before any employee begins maintenance or servicing of equipment where the unexpected energizing, start-up, or release of stored energy could cause injury, the equipment will be shut down, isolated from all potentially hazardous energy and locked or tagged out. **SEE LOCKOUT/TAGOUT PROGRAM.**
- Log stackers and front-end loaders should carry loads as low as possible to maintain stability.
- Before unloading a truck ensure driver is in the clear and in view of the log unloader operator.
- Wrappers must be left in place until the load is secured to prevent logs from falling off load.
- Only authorized persons are allowed to operate equipment.
- No person shall approach the immediate vicinity of a log-handling machine without first notifying the operator of the person's intention and receiving an acknowledgement from the operator that it is safe to approach.
- Riding on any part of a log-handling machine except under the canopy guard is prohibited.
- Persons shall not position themselves in the hazardous area near or under loads of logs being lifted, moved or suspended.

This material was produced under grant number SH20866SH0 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government.